



5MP IP Indoor Camera



Features:

- 5MP HD resolution, clear and fine images;
- Support 2D/3D noise reduction, digital wide dynamic;
- Advanced H.265/H.264 video compression, Super low rate, high definition quality of image;
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.
- Support ONVIF; access third party;
- Support various mobile monitoring (iPhone, Android);
- Provide web、CMS、center platform management software MYEYE, provide SDK development
- Support cloud technology, easy to achieve network penetration, fro in-line and alarm information pushed

Model	XP-1464C50-IP-PoE
System structure	Embedded RTOS, dual-core 32bit DSP (Hi3516EV100), pure hard compression, watch dog
Sensor	1/2.9" low illumination CMOS sensor
Video compression	H.265/H.264, support dual stream, AVI; 0.1M~8Mbps variable; 1~30f/s variable
Image output	Main stream: 2592*1944@15fps, 1920*1080@20fps; sub-stream: 1280*720@25fps;
LED	18 smart IR range upto 10 to 15 mtr
Shutter	1/50(1/60)s to 1/10,000s
Lens	3.6mm fixed lens
Day and night	Support IR-CUT
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	N/A
Network interface	1* RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc
Extension interface	N/A
Singal interface	One photo resistance interface, one IR-CUT interface, support photo resistance signal and IR-CUT links to IR
PTZ	N/A
Motor interface	N/A
Alarm I/O	1/0 (support alarm input and video link to background)
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	N/A
Other function	Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software、MYEYE; perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC12V/2A input, power consumption: ≤3W, □
Other	Support POE power supply
Certification	CE, FCC, RoHS, BIS