



3MP IP Outdoor Camera



Features:

- 3.0M star-light illumination HD resolution,clear and fine images, Autofocal;
- Support multiple intelligent analysis;
- Support 2D/3D noise reduction,digital wide dynamic;
- Advanced H.265/H.264 video compression,Super low rate,high definition quality of image;
- Professional anti-lightning,conform to GB/T17626.5 and IEC61000-4-5。
- Support ONVIF ,access third party ;
- Support various mobile monitoring(iPhone,Android);
- Provide web、CMS、center platform management software MYEYE,provide SDK development
- Support cloud technology,easy to achieve network penetration,fro in-line and alarm information pushed

| Model | XP-2633C30-IPE POE STL |
|---------------------------|--|
| System structure | Embedded RTOS,dual-core 32bit DSP(Hi3516CV300),pure hard compression , watch dog |
| Sensor | 3.0M 1/2.8" IMX307 star-light illumination CMOS sensor ,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2 |
| Video compression | H.265/H.264,support dual stream,AVI;0.1M~8Mpbs variable;1~30f/s variable |
| Image output | Main stream: 1920*1080@25fps, 1280*720@25fps; sub-stream: 704*576@25fps; |
| LED | 4warm Arrey Smart IR range upto 20 to 25 mtr |
| Shutter | 1/50(1/60)s to 1/10,000s |
| Lens | 3.6mm/ 6mm {optional} fixed lens |
| Day and night | Support IR-CUT |
| Noise reduction | Support 2D/3D |
| Wide dynamic | Support |
| Auto iris | N/A |
| Network interface | 1*RJ45 10/100M adaptive Ethernet port;support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc |
| Extension interface | 1*USB,support WIFI/3G,support SD ; 1ch Alarm output ; reset key ; 1ch Alarm input or LED panel ; RTC battery |
| Singal interface | One photo resistance interface,one IR-CUT interface ,support photo resistance signal and IR-CUT links to IR |
| Alarm I/O | 1/0(support alarm input and video link to background) |
| Reliability Comprehensive | lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing |
| Intelligence analysis | Alarm line,alarm region,goods stranded,video block,fuzzy detection,scene change |
| Other function | Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage.support JPEG capture ; united remote client monitoring sofaware、MYEYE;perfect SDK; |
| ONVIF | Support |
| Mobile monitoring | Support multiple mobile monitoring (iOS, Android) |
| Power | DC12V/2A input, power consumption:≤3W, |
| Other | Support POE power supply (optional) |