




2.0 MP 4G Pan-Tilt



Features:

- Adopt high performance 1/2.8" CMOS;
- Adopt high performance imported dot matrix large glass lamps and imported high-speed glass lamp light, to ensure the IR distance 150m; product life can reach 30,000 hours;
- Intelligent infrared control technology can automatically control the infrared light according to the environment. Under the premise of ensuring monitoring results, it can effectively enhance the infrared lamp's life and ensure the product stability;
- Constant current circuit design, to ensure stable operation of the infrared light. It won't reduce the infrared lamp's life which caused by the changing of the power supply;
- Efficient cooling structure, using physical means heat, which can effectively reduce the temperature of the inside dome camera, to prevent the inner to be fogging, and to ensure the machine's stability.

Model No.	XP-4420F20-WiFi-4G
Image sensor	1/2.8" CMOS
Signal model	PAL/NTSC
Horizontal resolution	1080P
Effective pixel	1920 (H) x1080 (V)
Minimum illumination	Color:0.01Lux B/W:0.001Lux
S/N radio	>50dB
Backlight compensation	On/Off
White balance	Auto
Electronic shutter	PAL:1/50~1/10000s NTSC:1/60~1/12000s
Focus length	5~90mm
Optical focus	36x
Focus system	Auto/Manual/Auto zoom
Presets	255pcs
Patrol track	4 groups, each group record 3min.
Cruise track	4 groups, each group for 16 presets
IR distance	150M
Horizontal range	360°continuous rotation
Vertical range	-90°-0°
Manual call speed	0.01°-180°/s
Protocol	PELCO D,PELCO P
Presets call speed	Max. 200°/s
synchronization system	Inner synchronization / power supply synchronization
IR life	30000 hours
Support	AB preset scan, patrol scan, idle function, focus zoom, timer function, subject of dome camera
IR light angle	Infrared zoom matching technology
IR light power	Auto
IR system	Auto/Color/Black and white
Cooling structure	Dustproof structure outside the circle
Fan control	ICR
Menu	Chinese/English
Power supply	DC12V/4A
Protection level	IP66
Work temperature	-35°C~+65°C