



8 Ports Non-PoE Full Giga Switch



Main Features:

- 8*1000M Ethernet ports with auto-negotiation function
- Support 1000M speed rate, MDI/MDIX and half/full-duplex with auto-negotiation function
- Each port has the complete LED Indicator light
- Support single mode single fiber, single mode dual fiber, multi-mode dual fiber and SFP slot
- Support IEEE802.1d Spanning Tree
- Each port supports wire-speed switching, 64~1518 frame length can reach the wire speed
- Support 9216bytes Jumbo packet
- Internal 4K MAC Address Entities
- Support high performance QoS function on each port
- Support multicast to avoid network congestion
- Support 5-16V voltage input
- Support 4KV port lightning protection
- Require no configuration and will instantly operate as soon as you power it up
- Use low-power consumption chips, only 2.5W in full load conditions

Dimensions:



Model No.	XP-SW2008-FG	
Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3ab 1000Base-T	IEEE802.3x Flow control IEEE802.1p QoS IEEE802.1d Spanning Tree
Certifications	CCC, CE, FCC, RoHS	
Ethernet Port	Connector: RJ45 Data Rate: 10/100/1000M Distance: 100m UTP Type: UTP-5E or higher level	
Performance	Processing Type: Store and Forward Transmission Mode: half/full-duplex with auto-negotiation function MAC Table Size: 4K Buffer Space: 1Mbit Back bandwidth: 16G Time Delay: <20μs	
Power	Power Type: external power supply Input Voltage: AC100V~240V 50/60Hz Connector: DC Socket Working Voltage: 5V Power Consumption: 1.8W~5W	
Environment	Storage Temperature: -40~70°C Operating Temperature: -10~55°C Relative Humidity: 5-90% (no condensation)	
Warranty	1 year	
Physical Characteristics	Dimension: 152×83.5×30mm Weight: 0.30kg Color: Metal, Blue	