



8 Port Outdoor PoE



Key Feature:

- Using Cat 5 network cable support power to the Access Point and IP Camera.
- Networking Standard: IEEE802.3 at/af.
- Long distance transmission and power supply maximum transmission distance is 130m.
- Upload port support Auto MDI/MDIX.
- Forwarding Mode: Store and forward.
- Intelligent power distribution and secure power supply system.
- Power circuit protection function can protect equipment.
- Zero configuration feature power supply is automatically supplied to the adaptive equipment.
- 6KV Professional thunder design, overtemperature protection, short circuit protection, high reliability, high stability.
- Nature cooling, small, compact, mute all the designs are convenient for you to put.
- Reduce the no load loss.

Model No.	XP-SW4808-PoE
Network Interface	PoE(1-8)
Transmission Rate	100Mbps Full Duplex; 10 or 100Mbps Half Duplex
	Network Interface: 10BASE-T or 100BASE-TX RJ45 port of Ethernet
Performance & Specification	Bandwidth : 1.6 Gbps (no barriers)
	Network Latency(10 to 100Mbps): $\leq 20\mu s$ (use the 64 byte package size)
	MAC address table: 2K
	The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE802.3i10BASE-T
	IEEE802.3u100BASE-TX
	IEEE802.3xFlowControl
	IEEE802.3af/at Power over Ethernet
Power Cable	Default: 1/2(+), 3/6(-); (Can Be Selected 4/5(+), 7/8(-))
LEDs Light	PWR Light always on
Power Support	Power input:AC 180~240V 120W
	Power input PoE port 1-8,1/2 (+52V),3/6(GND)
Physical	Size(L*W*H):310mm*260mm*100mm
Working Environment	Operating Temperature:-10°C~55°C (-14°~131°F)
	Storage Temperature:-40°C~70°C (-104°~158°F)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Electromagnetic Compatibility	CE mark
	FCCPart15, Class B
	VCCI ClassBEN55022 (CISPR 22)
	C-Tick
Warranty	Whole machine: 2 year
Package Content	AC Power Cable 、 Installation Manual Warrantly Card

SMART Outdoor Poe Switch

- PoE Watchdog
- PoE+ support 60W
- 100/1000M Hybrid PoE
- Industrial grade Chip
- Green Networking
- 6KV Lightning Protection
- IP66
- 8KV ESD Protection
- Multiple Installations
- Temperature

Head Office: Xpia Electronics Pvt. Ltd. | Sales: 9890241320, 9205313662 | Technical Support: 9890241321, 9890241322