



## 4MP IP Outdoor Camera



### Features:

- Supporting Face detection, Humanoid detection, and supports customization of other smart functions.
- 4.0MP HD Low illumination resolution, clear and fine images.
- Support 2D/3D noise reduction, digital wide dynamic.
- Advanced H.265(Compatible with H.264) video compression, Super low rate, high definition quality of image.
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.
- Support ONVIF; access third party. Support various mobile monitoring (iPhone, Android).
- Provide web, CMS, center platform management software MYEYE, provide SDK development.
- Support cloud technology, easy to achieve network penetration, fro in-line and alarm information pushe.

| Model                 | XP-2683C40-IP  |
|-----------------------|--|
| System structure      | Embedded RTOS, dual-core 32bit DSP(NT98562), pure hard compression, watch dog  |
| Sensor                | 4.0M 1/3"SC401AI Low illumination CMOS sensor, color 0.01Lux@F1.2, black/white 0.001Lux@F1   |
| Video compression     | H.265(Compatible with H.264), support dual stream, AVI; 0.1M~8Mbps variable; 1~30f/s variable  |
| Image output          | Main stream: {4MP} 2560*1440@25fps, {3MP} 2304*1296@25fps, {2MP} 1920*1080@25fps; sub-stream: 800*448@25fps;   |
| LED                   | 18 smart IR range upto 20 mtr  |
| Shutter               | 1/50(1/60)s to 1/10,0  |
| Lens                  | N/A  |
| Day and night         | Support IR-CUT, IR-CUT coil has an internal resistance of 20 ohms, the power-on time is less than 200ma, and the voltage is 3.5V-6V  |
| Noise reduction       | Support 2D/3   |
| Wide dynamic          | Support digita   |
| Auto iris             | N/A  |
| Network interface     | 1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/DHCP/NTP/UPnP etc  |
| Extension interface   | N/A  |
| Singal interface      | One photo resistance interface, one IR-CUT interface, support photo resistance signal and IR-CUT links to IR   |
| Audio Interface       | 1 Mic {Optional}   |
| PTZ                   | N/A  |
| Motor interface       | N/A  |
| Alarm I/O             | N/A  |
| Reliability           | Comprehensive lightning protection, 7 * 24 hours -10°C~65°C high temperature stable and reliable t   |
| Intelligence analysis | Supporting Face detection, Humanoid detection, and supports customization of other smart functions etc   |
| Other function        | Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software, MYEYE; perfect SDK; |
| ONVIF                 | Support  |
| Mobile monitoring     | Support multiple mobile monitoring (iOS, Android)  |
| Power                 | DC 12V/2A input, power consumption: ≤3W,   |
| Other                 | Support POE power supply, not support any custom, The drive voltage of the light boa   |
| Certification         | CE, FCC, RoHs, BIS   |